

PLS6MW Platform

Expanded Material Possibilities

For the maximum in material processing versatility, consider the PLS6MW Multi-Wavelength Laser Platform. Unique among laser systems, the PLS6MW can make use of three different laser wavelengths to process the broadest spectrum of materials and applications. The Multi-Wavelength capability of the PLS6MW can be used to accomplish tasks that are impossible using only a single wavelength.

1.06 micron wavelength – Fiber Laser

The PLS6MW can mark most metals and some plastics when configured with a 1.06 μm pre-aligned fiber laser.

10.6 micron wavelength – CO₂ Laser

The full breadth of organic and inorganic material processing capabilities are realized when the PLS6MW is configured with a standard pre-aligned 10.6 μm CO₂ laser.

9.3 micron wavelength – CO₂ Laser

For excellent results on certain plastics, the PLS6MW can be reconfigured with an interchangeable, pre-aligned 9.3 μm CO₂ laser.



Laser Technology Benefits

- ▶ **Software Controlled** - Any Windows[®]-based software with a print function can be used with the laser system.
- ▶ **Multi-Material** - Process an endless number of materials.
- ▶ **Multi-Process** - Cut, engrave, mark and produce photo images in one step.
- ▶ **Non-Contact** - Modify material without applying any physical force.
- ▶ **On-Demand** - Produce everything you need in real time, without waiting for hard-tooling.

Uniquely Universal Features

▶ **Laser Sources**

Our patented, metal core, air-cooled, free-space slab, CO₂ lasers produce excellent beam quality with even power distribution, good near-field and far-field characteristics and long life. Dual lasers dramatically increase speed, edge quality and power.

▶ **Rapid Reconfiguration™**

Unique to ULS, Rapid Reconfiguration allows our modular platforms to be field-reconfigured with a variety of laser sources, in seconds, and without tools. Easily exchange laser wavelengths or wattage to change power, increase speed and throughput.

▶ **High Power Density Focusing Optics™**

High Power Density Focusing Optics (HPDFO™) focuses the laser beam to the smallest spot size available, producing images with tighter tolerances, making even miniscule engraving details sharp.

▶ **1-Touch Laser Photo™**

1-Touch Laser Photo is our popular software package that makes it quick and easy to reproduce stunning photographic images on nearly any material.

▶ **Multi-Wavelength Technology**

The PLS6MW has been engineered to support interchangeable CO₂ laser sources that produce 10.6 μm and 9.3 μm of laser energy at various power levels, and a fiber laser source that produces 1.06 μm of laser energy.

System Specifications

PLS6MW	
▶ Work Surface Area (WxH)	32 x 18 in (813 x 457 mm)
▶ Maximum Part Size ¹ (WxHxD)	37 x 23 x 9 in (940 x 584 x 229 mm)
▶ Dimensions (WxHxD)	44 x 39 x 36 in (1118 x 991 x 914 mm)
▶ Rotary Capacity	Max. Diameter: 8 in (203 mm).
▶ Motorized Z-Axis Lifting Capacity	40 lbs (18 kg)
▶ Available Focus Lenses	2.0 / 4.0 / HPDFO™
▶ Laser Platform Interface Panel	Keypad and LCD display shows current file name, laser power, engraving speed, PPI and run time.
▶ Computer Requirements	Requires dedicated PC with Windows® 7/8/10 32/64 bit and one available USB port (2.0 or higher).
▶ Cabinet Style ²	Free-standing
▶ Laser Options	CO ₂ (10.6 μm): 10, 25, 30, 40, 50, 60, 75 W CO ₂ (9.3 μm): 30, 50, 75 W Fiber (1.06 μm): 40, 50 W
▶ Approximate Weight	325 lbs (147 kg)
▶ Power Requirements	110V/10A; 220V-240V/5A
▶ Exhaust Connection	Two 4 in (102 mm) ports 500 CFM @ 6 in static pressure (850 m ³ /hr at 1.5 kPa).

USA

7845 E. Paradise Lane
Scottsdale, AZ 85260

+1 480-483-1214
moreinfo@ulsinc.com

Japan

The Yokohama Landmark Tower
15th Fl. 2-2-1-1 Minato Mirai
Nishi-ku Yokohama-shi
Kanagawa-ken 220-8115 JAPAN

+81 45-224-2270
japansales@ulsinc.com

Europe/Middle East/Africa

Lerchenfelder Gürtel 43
1160 Vienna, Austria

+43 1-402-22-50
eurosales@ulsinc.com

UNIVERSAL[®]
LASER SYSTEMS

Learn more at ulsinc.com

CDRH Class 1 safety enclosure for CO₂ and Fiber lasers². Class 2 for red laser pointer.

¹ Maximum part size defined as used with 2.0 lens.

² CDRH Class 1 laser safety enclosure provides for safe operation without the need for an interlocked room or protective eyewear.



WARNING: UNIVERSAL LASER SYSTEMS PRODUCTS ARE NOT DESIGNED, TESTED, INTENDED OR AUTHORIZED FOR USE IN ANY MEDICAL APPLICATIONS, SURGICAL APPLICATIONS, MEDICAL DEVICE MANUFACTURING, OR ANY SIMILAR PROCEDURE OR PROCESS REQUIRING APPROVAL, TESTING, OR CERTIFICATION BY THE UNITED STATES FOOD AND DRUG ADMINISTRATION OR OTHER SIMILAR GOVERNMENTAL ENTITIES. FOR FURTHER INFORMATION REGARDING THIS WARNING CONTACT UNIVERSAL LASER SYSTEMS OR VISIT WWW.ULSINC.COM.

ULS laser systems are protected under one or more of U.S. Patents: 5,661,746; 5,754,575; 5,867,517; 5,881,087; 5,894,493; 5,901,167; 5,982,803; 6,181,719; 6,313,433; 6,342,687; 6,423,925; 6,424,670; 6,983,001; 7,060,934; 7,415,051; 7,469,000; 7,715,454; 7,723,638; 7,947,919; 8,101,883; 8,294,062; 8,599,898; 8,603,217; 8,101,883; 8,294,062; 8,599,898; 8,603,217; 9,155,988; 9,263,844; 9,263,845; 9,281,649; 9,346,122; 9,354,630; D517,474. Other U.S. and international patents pending. Made in the U.S.A.

©2017 Universal Laser Systems. All Rights Reserved. The Universal Laser Systems logo and name are registered trademarks of Universal Laser Systems, Inc. All other company and product names are trademarks or registered trademarks of their respective companies.

MC013-0715 REV2017.03